



量程1 测量范围:0-1500um,精度 : ±1-3%或±2.5 um,分辨率:0.1um(0-100um),1um(100-1500um)

精度:取其大者

探头样式	铁基F	非铁基NF	两用型FNF	最小净空高度		最小样本直径	
直探头	T456CF1S	T456CN1S	T456CFNF1S	F,N 85mm	FNF 88mm	F,N,FNF(F) 4mm	FNF(N) 6mm
直角探头	T456CF1R	T456CN1R	T456CFNF1R	F,N 28mm	FNF 38mm	F,N,FNF(F) 4mm	FNF(N) 6mm
微型M5-90度探头45mm	T456CFM5R90A	-	-	F 16mm		F 4mm	
阳极氧化型	-	T456CN1AS	-	N 100mm		N 4mm	
PINIP™探头	T456CF1P	T456CN1P	T456CFNF1P	F 170mm	N,FNF 180mm	F,N,FNF(F) 4mm	FNF(N) 6mm

量程2 测量范围:0-5mm , 精度:±1-3%或20um , 分辨率 : 1um:0-1mm;10um(1-5mm)

直探头	T456CF2S	T456CN2S	-	F 89mm	N 88mm	F 8mm	N 14mm
直角探头	T456CF2R	-	-	F 32mm		F 8mm	
铠装探头	T456CF2ARM	-	-	F 138mm		F 8mm	
可伸缩探头56-122cm	T456CF2T	-	-	F 36mm		F 8mm	
软涂层探头	T456CF2B	-	-	F 89mm		F 8mm	
防水探头(1米线)	T456CF2SW	-	-	F 138mm		F 8mm	
防水探头(5米线)	T456CF2SW-5	-	-	F 138mm		F 8mm	
防水探头(15米线)	T456CF2SW-15	-	-	F 138mm		F 8mm	
防水探头(30米线)	T456CF2SW-30	-	-	F 138mm		F 8mm	
防水探头(50米线)	T456CF2SW-50	-	-	F 138mm		F 8mm	
PINIP™探头	T456CF2P	T456CN2P	-	F 174mm	N 185mm	F 8mm	N 14mm
高温探头(250度)	T456CF2PHT	-	-	F 174mm		F 8mm	

量程3 测量范围:0-13mm,精度:±1-3%或50um,分辨率 : 1um : 0-2mm,10um:2-13mm

直探头	T456CF3S	-	-	F 102mm		F 14mm	
PINIP™探头	T456CF3P	-	-	F 184mm		F 14mm	

量程0.5 测量范围:0-500um,精度:±1-3%或2.5um,分辨率:0.1um:0-100um,1um(100-500um)

45mm mini探头	T456CFM3-A	T456CNM3-A	-	F 6mm	N 6mm	F 3mm	N 4mm
45mm mini直角探头	T456CFM3R90A	T456CNM3R90A	-	F 16mm	N 16mm	F 3mm	N 4mm
45mm mini45度探头	T456CFM3R45A	-	-	F 18mm		F 3mm	
150mm mini直角探头	T456CFM3R90C	T456CNM3R90C	-	F 16mm	N 16mm	F 3mm	N 4mm
150mm mini45度探头	T456CFM3R90D	-	-	F 16mm		F 3mm	
300mm mini直角探头	T456CFM3R45D	-	-	F 18mm		F 3mm	
300mm mini45度探头	-	T456CNM3R90E	-	N 16mm		N 4mm	

热线:020-38498255

www.tintron.cn

